

## STANDARD FEATURES

- 2 year Warranty
- 24V class 2 control circuit with 40VA transformer to protect against short circuit
- On board receiver with antenna
- External radio control terminal strip
- Low friction powder metal limit cam nuts with fully adjustable rotary type limit switch assembly
- Three button open-close-stop control station Nema-1
- Continuous duty industrial motor with external reset overload protection (1-phase or external thermal overload relay motor protection (3-phase)
- Motor removable without affecting limit settings
- Heavy duty worm gear reduction in oil bath gearbox
- 1.5 second time delay on all open functions standard on 1.5, 2, 3, & 5 HP
- Solenoid brake standard
- #50 roller chain and sprockets on final drive, except 3 HP or larger
- Emergency chain hoist with electrical cut-out switch for manual operation
- Chain keeper
- Universal left or right hand mounting
- Baked on dark grey coat finish
- Shipping weight 115 lbs
- N-1 Micanan photocells included for doors up to 24' wide



**When ordering a PRO-GH operator, supply the following information:**

- Door height
- Door width
- Type of door
- Horsepower
- Voltage/ Phase
- Safety devices
- Door shaft diameter & door shaft key size
- Mounting (LH or RH, Bracket or Wall mount)
- Control circuit options (see page 5-6)

