## PRO-LT COMMERCIAL LIMITED DUTY BELT DRIVE TROLLEY OPERATOR Designed for use on extra

Designed for use on commercial doors with standard lift tracks that require no more than 15 cycles per hour

## STANDARD FEATURES

- 2 year Warranty
- 24V class 2 control circuit with 40VA transformer to protect against short circuit
- External radio control terminal strip
- Low friction powder metal limit cam nuts with fully adjustable rotary type limit switch assembly
- Three button open-close-stop control station Nema-1
- 1/2 HP high starting torque, instant reversible motor protected by internal automatic thermal overload device
- Motor removable without affecting limit settings
- Heavy duty 4L V-belt
- #41 roller chain & sprockets on all internal drives
- Adjustable friction clutch
- 3/4" permanently lubricated & sealed ball bearings on pulley shaft
- 1" permanently lubricated & sealed ball bearings on final drive shaft
- Solenoid brake available (optional PRO-LTB)
- Emergency quick release disconnect for manual operation
- #410 roller chain drive on trolley rail assembly
- Trolley track for doors up to 12' standard
- Door speed 9" per second
- Baked on dark grey coat finish
- Shipping weight 60 lbs (excludes rails)
- For use on doors up to 16' high
- N-1 Micanan photocells included for doors up to 24' wide



## When ordering a PRO-LT operator, supply the following information:

- Door height
- Door width
- Voltage/ Phase
- Safety devices
- Control circuit options (see page 5-6)

