


INSTALLATION INSTRUCTIONS

RECEIVER INSTALLATION


A. USING TERMINAL MOUNTING BRACKETS

Mount the receiver directly on the operator with three terminal mounting brackets packaged with the receiver (See Figure 1).



B. USING MOUNTING CLIP

A mounting clip is packaged with each receiver. To install the receiver, attach the clip to the mounting surface with screws. Position the two rectangular holes on the back of the receiver over the clip and snap the receiver down into place (See Figure 2).



NOTE:

1. Straighten the antenna wire on receiver with end of wire toward floor.
2. Keep antenna away from adjacent metal objects for maximum performance.

TRANSMITTER INSTALLATION

A clip is supplied so that the transmitter may be mounted in the automobile at the sun visor. When using the clip, fit its two knobs into the two holes on the back side of transmitter.

BATTERY INSTALLING

Please find attached battery and remove the battery cover on the back side of transmitter. Then, snap the battery into it's connector.

CODE SETTINGS

All code settings are pre-set at the factory to the same ON/OFF positions. Codes should be re-set to prevent operation of other units installed close by. Use a pencil or ball point pen to set the ten keys on the transmitter and receiver to the same ON/OFF positions.

For example, if the selected code is:

1	2	4	6	7	9	10
---	---	---	---	---	---	----

The switch appears:

	1	2	3	4	5	6	7	8	9	10
ON	■	■		■		■	■		■	■
			■		■			■		

CAUTION: Never set all ten keys in the ON position or OFF position. In the example above, these keys are set as shown by the small rectangular symbols.

HOW TO ORDER REPAIR PARTS

DEVANCO CANADA

19192 HAY ROAD, UNIT Q
SUMMERSTOWN, ON K0C 2E0

TOLL FREE: 855-931-3334

www.devancocanada.com

**WHEN ORDERING REPAIR PARTS
PLEASE SUPPLY THE FOLLOWING INFORMATION:**

- ✓ PART NUMBER**
- ✓ DESCRIPTION**
- ✓ MODEL NUMBER**