### MANARAS RADIO022

## PROGRAMMING INSTRUCTIONS FOR MODEL MT3-1000

Remove the back cover from the transmitter and receivers for access to the code switches. Inside in a 10-bits dip switch exposed on the circuit board. Use a pencil or ball-point pen to set the 10-bits dip switch of your choice. But, note that bits numbered 8, 9, 10 are not operational on the transmitter.

#### TRANSMITTER:

Determine the bits numbered 1 - 7 to ON/OFF position. For example, set bits numbered 1, 3, 5 to ON and numbered 2, 4, 6, 7 to OFF (for example, refer to the table below)

1	2	3	4	5	6	7	8	9	10

#### ASSOCIATED RECEIVERS

There are 3 coded receivers controllable by this channel transmitter. Set the bits as below

1st Receiver: set the bit numbered 8,10 to ON, numbered 9 to OFF and the others bits to the same ON/OFF position as the corresponding bits in the transmitter (for example, refer to the table below).

1	2	3	4	5	6	7	8	9	10	ON
										lT

2<sup>nd</sup> Receiver: Set the bit numbered 8 to ON and 9, 10 to OFF and others bits to the same ON/OFF position as the corresponding bits in the transmitter (for example, refer to the table below)

1	2	3	4	5	6	7	8	9	10	ON

3rd Receiver: Set the bits numbered 8, 9 to ON, numbered 10 to OFF and the others bits to the same ON/OFF position as the corresponding bits in the transmitter (for example, refer to the table below).

1	2	3	4	5	6	7	8	9	10	ON



### **IMPORTANT**

Be sure all are set to the definite code, since a different setting of just one dip switch will prevent operation

# HOW TO ORDER REPAIR PARTS

# **DEVANCO CANADA**

19192 HAY ROAD, UNIT Q SUMMERSTOWN, ON K0C 2E0

TOLL FREE: 855-931-3334

www.devancocanada.com

WHEN ORDERING REPAIR PARTS
PLEASE SUPPLY THE
FOLLOWING INFORMATION:

- **✓ PART NUMBER**
- ✓ DESCRIPTION
- ✓ MODEL NUMBER