

811LMX / 813LMX 892LT / 894LT

Programmable DIP and Learning Remote Controls



Provide convenient access to gated communities, industrial facilities, and commercial sites with the right remote control solution for your application.

PRODUCT GUIDE

Popular Features

Learning Remote Controls

Easy Independent Button Programming allows for each button to be programmed with different frequency and codes.

Eliminate the need for multiple remotes when operating LiftMaster® Garage Door Openers, Gate Operators, Commercial Door Operators or myQ® Accessories.

Cloning capability of existing LiftMaster DIP Switch Remote Controls (61LM and 361LM) or a LiftMaster encrypted DIP Switch remote control (811LM) to any button as well as the 811LMX Programmable DIP in any of the above modes.

Flexible compatibility with direct programming to Security+ 2.0 and Security+ Rolling code technology for security and dependability.

Programmable DIP Remote Controls

Both 811LMX and 813LMX allow up to 4096 unique codes with the 12-position DIP. 813LMX uniquely designed for open/close/stop functionality for commercial door applications.

Compatible with LiftMaster gate operators, commercial door operators and receivers. Can be programmed to the following DIP modes: Security+2.0 Encrypted DIP (default), legacy 315 MHz or legacy 390 MHz.

For more information, please visit www.devancocanada.com
or call toll free at 855-931-3334

LiftMaster

POWERED BY myQ

Specifications

892LT

2-Button Security+ 2.0® Learning Remote Control

894LT

4-Button Security+ 2.0® Learning Remote Control

Compatibility

Code / frequency for direct programming:

- Security+ 2.0® – Default
- Security+® 315 MHz
- Security+ 390 MHz

Code / frequency for cloning 811LMX Programmable DIP (in the below modes):

- 811LM Encrypted DIP Switch
- 361LM DIP Switch 315 MHz
- 61LM DIP Switch 390 MHz

Power

Battery (included): AAA battery

Dimensions

3.2" W x 1.75" H x .07" D

Radio

- Security+ 2.0 (Default)
- Security+ 315 MHz
- Security+ 390 MHz
- Clone Capability: 811LM, 361LM, 61LM, 811LMX

Operating Temperature

-40 °F (-40 °C) to 149 °F (65 °C)

Shipping Weights

.16 lbs.

Carton Contents

Remote control, visor clip, instruction manual

Storage / Ship Temperature

-40 °F (-40 °C) to 185 °F (85 °C) @ 50% Rh

Warranty

1 Year Limited

811LMX*

- Single Button Programmable DIP Remote Control

813LMX †

- 3-Button OCS (Open/Close/Stop) Programmable DIP Remote Control

Compatibility

Code / frequency for direct programming:

- Encrypted DIP (Default)
- 315 MHz DIP
- 390 MHz DIP

Power

Battery (included): Coin Cell 3V – CR2032 type

Dimensions

3.125" W x 1.75" H

Radio

- Security+ 2.0 Encrypted DIP (Default)
- 315 MHz DIP Switch
- 390 MHz DIP Switch

Operating Temperature

-40 °F (-40 °C) to 149 °F (65 °C)

Shipping Weights

.22 lbs.

Carton Contents

Remote control, visor clip, instruction manual

Storage / Ship Temperature

-40 °F (-40 °C) to 185 °F (85 °C) @ 50% Rh

Warranty

1 Year

* Replaces 811LM, 361LM, 61LM, 61LMC Remote Controls providing the same functionality

† Replaces 813LM, 333LM, 33LM Remote Controls providing the same functionality