

D-TEK BOX

VEHICLE LOOP DETECTOR

Applications

EMX have designed the new D-TEK Vehicle Loop Detector with the following objectives in mind:

1. Allow for easy installation into small operator housings.
2. All the controls must be accessible from the outside for easy installation and operation.
3. Detector must operate reliably with marginal loops.
4. Provide all the features and controls necessary for a variety of applications.
5. Use metal housing for maximum durability and RF blocking.
6. Provide maximum surge protection on all inputs and outputs of the detector.

D-TEK BOX



EMX Industries, Inc.
4564 Johnston Parkway, Cleveland, Ohio 44128

For more information,
please visit www.devancocanada.com
or call toll free at 855-931-3334

Indicators & Controls

- **Power** The detector is available in the following voltages, 12V AC/DC, 24V AC, 24V DC, 110V AC, 220V AC. Maximum current draw 100mA
- **Low Power Detector** is available with maximum current draw of 60mA
- **Power Indicator** Green LED solid light indicates power
- **Loop Failure Indicator** Green LED blinks indicates loop problem In fail secure mode relay 2 will indicate loop fail
- **Loop Failure Memory** Green LED blinks with fast consecutive blinks indicates past loop problem that healed
- **Detect Indicator** Red LED solid light indicates detection
- **Extend Indicator** Red LED blinks after a car left the loop indicates time extend feature

Accessories



Harn-11



LD-11



PR Loop

Technical Data

Temperature
Environmental Protection
Enclosure

Output Relays
Connector
Surge Protection
Loop Input
Grounded Loop
Loop Inductance Range

Tuning
Tracking
Sensitivity
Frequency

Infinite Presence Mode
Limited 4 Minutes
Presence Time

Second Presence Relay
Pulse On Exit / Entry
Fail Safe / Secure

Filter
Extended Detection

-40° F to + 180° F

Circuit board is conformally coated

Extruded anodized aluminum,

Height = 3.25 inches 83 mm – Width = 2.56 inches 40 mm – Depth = 3.65 inches 90 mm

5A/125 V AC standard version, 1A/125 V AC low current version

86CP11 compatible with 11 pin Octal DIN rail mountable socket or wire harness

The detector is protected with neon discharge lamps, zener diodes and surge arrestors

Transformer isolated

The loop isolation transformer allows operation with poor quality loops

20 to 2000 microhenries with Q factor of 5 or higher

Detector automatically tunes to the loop after power application or reset

Detector automatically tracks and compensates for environmental changes

Is set by 10 position rotary switch

Is set three position toggle switch

DIP switch selectable presence

DIP switch selectable presence

DIP switch selectable

DIP switch selectable

DIP switch selectable

DIP switch selectable

DIP switch selectable 2 seconds

DIP switch selectable 3, 6 and 9 seconds

Ordering Information

- D-TEK-12 12 VDC
- D-TEK-24VDC 24 VDC
- D-TEK-24VAC 24 VAC
- D-TEK-110 110 VAC
- D-TEK-120 110VAC W/piggyback plug
- D-TEK-110-MS 110VAC w MS connector
- HAR-11 11 Pin Harness 3 ft wire
- LD-11 11 PIN DIN Socket
- PR-XX Preformed loop XX = loop size in inches

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of sale to our customer. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship. Rev 2.1 07/09/08

For more information, please visit www.devancocanada.com or call toll free at 855-931-3334