



EL1SS

TELEPHONE INTERCOM AND ACCESS CONTROL SYSTEM

Simplicity. Durability. Exceptional Value.

The LiftMaster® EL1SS Telephone Intercom and Access Control System provides wired telephone intercom communication and secure access control at the gate or door. It is easy to install, and its rugged stainless steel housing provides reliable, durable performance year after year, all at an exceptional value. With the EL1SS, residents or small businesses can simply communicate with visitors, grant or deny access, all from the convenience of their phone.

Performance

- **Connects directly** to the existing residential home phone line so no additional monthly expenses are incurred.
- **Easy-to-install** design saves an average of 10 minutes on installation time over older models.
- **Simple design** makes it ideal for residents and visitors to communicate and grant or deny access.
- **Stainless steel faceplate** with black powder coated housing is attractive and tough.
- **Weather-resistant** and durable design is ideal for the outdoors.
- **Remote open** feature opens two entrances independently from your home or office.
- **Intercom mode** makes use of existing telephone systems, even if your customers have a “cellular only” home.
- **Unique ringing** lets your customers know when a visitor is calling from the gate or door.
- **Call waiting** allows your customers to answer an incoming guest call while on another line.
- **Call forward** allows your customers to greet visitors, even when they are not home.
- **Do not disturb mode** offers additional privacy and is activated easily on your customer’s phone.
- **Party mode** is designed to conveniently hold open the entryway.
- **200 (4-digit) unique, programmable entry codes** provide convenient assigned access.
- **2-year warranty.**

Safety and Security

- **Vacation mode** locks the system down when no one is home.
- **Durable metal keypad with green backlighting** increases visibility for nighttime viewing.
- **Call button** is illuminated so visitors can locate it easily.

Optional Accessories:



Gooseneck Pedestal (PED42)
42 in. pad mount pedestal, the 2x2 in. square pipe has a black powder coat finish, 11 ga. steel for long lasting durability.



Gooseneck Pedestal (PED64)
64 in. in-ground mount pedestal, the 2x2 in. square pipe has a black powder coat finish, 11 ga. steel for long lasting durability.

Specifications

POWER INPUT

UL listed: AC/DC adapter, 115 Vac input, 16Vdc, 2.5A, 40W output transformer included

RELAY OUTPUTS

Two (2) independently controlled (latched and timed) 10 Amp (Form C) relays

AUDIO CIRCUIT

Full Duplex voice communication

AUTO CALL

Auto- Call for dry contact call initialization

PROGRAMMING METHODS

Unit keypad or from touch-tone phone

ENTRY CODES

200 (4- digit) unique programmable entry codes

OPERATING TEMPERATURE

-4°F (-20°C) to 149°F (65°C)

STORAGE AND SHIPPING TEMPERATURE RANGE

-40°F (-40°C) to 185°F (85°C)

FACEPLATE

Brushed stainless steel

REAR HOUSING

Black powder coated stainless steel

REGULATORY

FCC part 15 , IC Compliant and Industry Canada

DESIGNED TO NEMA 3R

NEMA rating: 3R

TELEPHONE CONNECTIVITY

Compatible with common POTS lines to residence, business

TELEPHONE RINGER EQUIVALENCE NUMBER (REN)

REN is 0.5B

BYPASS BOARD

Included (ability to disconnect EL1SS and maintain house phone if required)

WARRANTY

Two Year Limited

DIMENSIONS

10 in. W x 6-1/4 in. H x 5-1/4 in. D