

## STANDARD FEATURES

- 2 year Warranty
- 24V class 2 control circuit with 40VA transformer to protect against short circuit
- On board receiver with antenna
- External radio control terminal strip
- Low friction powder metal limit cam nuts with fully adjustable rotary type limit switch assembly
- Three button open-close-stop control station Nema-1
- Continuous duty industrial motor with overload protection
- Motor removable without affecting limit settings
- Heavy duty 5L V-belt
- #41 roller chain & sprockets on all internal drives
- Adjustable friction clutch
- Solenoid brake standard
- #50 roller chain and sprockets on final drive
- 3/4" permanently lubricated & sealed flanged precision ball bearings on pulley shaft
- Second and final stage of reduction cast iron 1" flanged bearings permanently sealed and lubricated
- Emergency chain hoist with electrical cut-out switch for manual operation
- Chain keeper
- Left or right hand mounting (must specify at time of order)
- Baked on dark grey coat finish
- Shipping weight 110 lbs
- N-1 Micanan photocells included for doors up to 24' wide



---

### When ordering a PRO-HHD operator, supply the following information:

---

- Door height
  - Door width
  - Type of door
  - Horsepower
  - Voltage/ Phase
  - Safety devices
  - Door shaft diameter & door shaft key size
  - Mounting (LH or RH, Bracket or Wall mount)
  - Control circuit options (see page 5-6)
- 

