

## Datasheet

### IP-MDSF - PoE Multi-Tenant Station (Flush Mount)

#### Product Description

CDVI's intercom system provides video entry solutions for residential and commercial properties alike. With both IP and a free smartphone app, take advantage of a flexible, affordable and reliable security system.

The IP-MDSF is an outdoor station that can manage up to 500 tenants. It features a 170° fisheye camera, touchscreen menu and an integral dual technology card reader. The IP system facilitates connection through PoE, making the intercom system seamless and easy to use.



#### Key Features

- Built-in multi-technology card reader (125 kHz and 13.56 MHz)
- PoE
- 5" touch screen
- Surface mount
- Micro SD card port for backup
- 170° fisheye camera
- Also available in surface mount: IP-MDS

 Certification

 DEEE

**RoHS** Certification

 IP54

 14°F to 122°F  
(-10°C to 50°C)

## Product Specifications

|                        |                                                                  |
|------------------------|------------------------------------------------------------------|
| <b>Material:</b>       | Stainless steel panel                                            |
| <b>Mounting:</b>       | Surface                                                          |
| <b>Technology:</b>     | IP                                                               |
| <b>Card reader:</b>    | MIFARE® Classic 13.56 MHz & 125kHz proximity card reader         |
| <b>Camera:</b>         | Type 1/3.7" Ultra Sense, ISP with 77dB WDR<br>170° fish-eye lens |
| <b>Screen:</b>         | 800 x 480 pixels                                                 |
| <b>Unlocking time:</b> | 1 to 99s                                                         |
| <b>Relays:</b>         | 2                                                                |
| <b>Cable type:</b>     | Cat-5e or Cat-6                                                  |
| <b>Weight:</b>         | 2.2 lb, 1 kg                                                     |



## Electrical Specifications

|                           |                                                                                                  |
|---------------------------|--------------------------------------------------------------------------------------------------|
| <b>Power input:</b>       | PoE (IEEE 802.3af Class 0)                                                                       |
| <b>Lock power supply:</b> | 12 V DC, 250 mA<br>(Internal power - fail safe only)<br>(Dry contact - fail safe or fail secure) |

## Accessories



**IP-SDS**

PoE Single Door Station



**IP-MON**

PoE Touch Screen Monitor



**Download the app today!**

